



## 0-170-05 - LED Rear Marker Lamp 12/24V

Durite LED rear marker lamp.

Voltage: 12-24V

4 pcs red LEDs

Integral Superseal Connector

Material: PMMA Lens / ABS Base

IP67

E Marked R7

### WARNINGS

Before using this unit please read these instructions carefully. Take special care to follow the warnings and safety suggestions listed below. Keep these instructions for future reference

### SAFETY WARNING

1. Proper installation of this product requires the installer to have a good understanding of automotive electronics, systems and procedures.
2. If mounting this product requires drilling holes, the installer MUST be sure that no vehicle components or other vital parts could be damaged by the drilling process. Check both sides of the mounting surface before drilling begins. Also de-burr the holes and remove any metal shards or remnants.
3. Do not install this product or route any wires in the deployment area of your air bag. Equipment mounted or located in the air bag deployment area will damage or reduce the effectiveness of the air bag, or become a projectile that could cause serious personal injury or death. Refer to your vehicle owner's manual for the air bag deployment area. The User/Installer assumes full responsibility to determine proper mounting location, based on providing ultimate safety to all passengers inside the vehicle.
4. Do not attempt to activate or control this device in a hazardous driving situation.
5. This product contains either strobe light(s), halogen light(s), high-intensity LEDs or a combination of these lights. Do not stare directly into these lights. Momentary blindness and/or eye damage could result.
6. All connections must use waterproof connectors and any unconnected wires must be sealed to prevent water ingress via the wire core, failure to do this may result in premature failure and invalidate the warranty.
7. Use only soap and water to clean the outer lens. Use of other chemicals could result in premature lens cracking (crazing) and discoloration. Lenses in this condition have significantly reduced effectiveness. Inspect and operate this product regularly to confirm its proper operation and mounting condition.
8. It is recommended that these instructions be stored in a safe place and referred to when performing maintenance and/or reinstallation of this product.
9. For this product to operate at optimum efficiency, a good electrical connection to chassis ground must be made. The recommended procedure requires the product ground wire to be connected directly to the NEGATIVE (-) battery post.

## TECHNICAL SPECIFICATIONS

Type	Marker Lamp - Rear
Voltage	12-24VDC
LED's	4 Red LED's.
Power Consumption	0.36W at 12VDC, 0.96W at 24VDC
IP Rating	IP67
Material Construction	PMMA Lens, ABS Base
Weight	0.048Kg
Dimensions	Please see below
Operating Temperature	-40°C to +50°C
Certificate	R7

## TECHNICAL DRAWING

