



Rear Mount Number Plate Colour CCTV Camera Part 0-776-17



WARNINGS

Before using this unit please read these instructions carefully. Take special care to follow the warnings and safety suggestions listed below. Keep these instructions for future reference.

There are no user-serviceable parts within the unit, refer servicing to qualified service personnel.


PRECAUTIONS

- Please ensure you are familiar and comply with local traffic and driving regulations.
- **Connection** - The camera should only be connected to a Durite cctv system.
- **Heat** - Do not install the camera near heat sources.
- **Mounting** - Ensure the camera is facing the desired direction before fixing the camera base. If fixing to isolated return chassis the camera bracket should be isolated from the vehicle chassis.
- **Service** - The user should not attempt to service these units beyond that described in these instructions. All other servicing should be referred to an authorised service technician.

GENERAL

The camera has a CMOS image sensor which gives a high quality picture and its solid state circuitry provides extremely long life. Compact size and single connection make it easy to install. It is recommended that all camera lead connections are additionally sealed by either wrapping with a suitable tape or application of heat shrink sleeving. It is recommend to connect the system and test before fixing to ensure the correct field of view is displayed.

DIMENSIONAL DRAWING



SPECIFICATION

Product Type.....License plate backup camera
 Image Sensor.....1/3 inch Colorful CMOS
 Resolution (TV line)..... 480TV line
 Effective Pixels.....PAL 756(H) x 504(V)
 View Angle.....Horizontal(120°) ; Vertical (90°)
 TV System.....PAL
 Waterproof rating.....IP68
 Image Lens.....2.5mm
 Min illumination.....0 Lux
 Night Vision.....20ft
 Electronic Shutter..... 1-1/10000 seconds
 Current consumption.....Max.120mA
 Video output.....1.0vp-p, 75ohm
 Power voltage.....DC 12V
 S/N Ratio.....Better than 48db(AGC-OFF)
 Connector type.....4 PIN aviation
 Audio.....NO
 Operating Temp.....-20°C~70°C,RH95% MAX
 Storage Temp.....-30°C~75°C,RH95% MAX
 Certificates.....E Marked

Female Aviation Plug

