

TECHNICAL SPECIFICATIONS

Call 01255 555200 Email info@durite.co.uk Visit www.durite.co.uk



0-295-65 - Square 5 Function LED Combination Lamp

Durite's LED 5 Function (STOP/TAIL/DI/REFLEX/REGISTRATION) Rear Combination Lamp:

- Surface Mount
- Multi-voltage alternative for mixed fleet applications
- Highly durable polycarbonate lens, built to withstand the tough working conditions of any commercial vehicle
- CE, E Marked ECE Approved. R148 R150 R10 EMC. UKCA.

Additional Information:

Black = Negative -VE

Red = Stop

Yellow = DI

White = Tail + Reg





TECHNICAL SPECIFICATIONS

Call 01255 555200 Email info@durite.co.uk Visit www.durite.co.uk

TECHNICAL SPECIFICATIONS

Туре	Square LED 5 Function Rear Combo Lamp
Voltage	10-30VDC
Functions	STOP /TAIL / DI / REFLECTOR / REGISTRATION
Current Draw at 12VDC	Stop 0.12A / Tail + Reg 0.2A / DI 0.13A
Current Draw 24VDC	Stop 0.06A / Tail + Reg 0.1A / DI 0.07A
Power	Stop 1.5W /Tail 2.5W / DI 1.7W
IP Rating	IP67
Material Construction	PMMA, ABS
Weight	0.350Kg
Dimensions	See below diagram
Operating Temperature	-40° to +60°C
StorageTemperature	-40° to +60°C
Certificate	CE, ECE E Mark R148, R150, R10 EMC. UKCA

TECHNICAL DRAWING

