TECHNICAL SPECIFICATIONS

DURITE®

Call 01255 555200 Email info@durite.co.uk Visit www.durite.co.uk



0-300-30 - 4 Function LED Rear Combination Lamp

Durite's LED 4 Function (STOP/TAIL/DI/REFLEX) Rear Combination Lamp:

- Surface Mount
- Multi-voltage alternative for mixed fleet applications
- Highly durable polycarbonate lens, built to withstand the tough working conditions of any commercial vehicle
- Universal for both Left and Right sides
- CE, E Marked ECE Approved.

Additional Information: White = Negative -VE Red = Stop Brown = Tail Green = DI



THE TRUSTED QUALITY BRAND FOR PROFESSIONALS



TECHNICAL SPECIFICATIONS

Call 01255 555200 Email info@durite.co.uk Visit www.durite.co.uk

TECHNICAL SPECIFICATIONS

Туре	LED 4 Function Rear Combo Lamp (Universal L + R)
Voltage	10-30VDC
Functions	STOP / TAIL / DI / REFLECTOR
Current Draw at 12VDC	Stop 0.30A / Tail 0.15A / DI 0.18A
Current Draw 24VDC	Stop 0.15A / Tail 0.08A / DI 0.09A
IP Rating	IP67
Material Construction	РММА
Weight	0.180Kg
Dimensions	See below diagram
OperatingTemperature	-40° ~ 60°C
StorageTemperature	-40° ~ 60°C
Certificate	CE, ECE E Mark R3, R6, R7, R10 EMC

TECHNICAL DRAWING

