




0-420-17 - Driving Worklamp Bar with Position and Amber Warning

Durite Worklight Driving Lamp with Amber Warning LED's and Position Lamp. 12/24V. 120W OSRAM LED, 10,080 Lumens (3580 Effective). 2010 LUX at 10M. 5700k Colour Temperature. IP68/IP69k. PC Lens, Aluminium Housing, SS304 Brackets. 60cm Fly Lead with 6PIN DT Connector. Size: 357*70*67mm. E Marked R10 (EMC), R7 (POS), R112 (Driving) and R65 (Warning).

Fly Leads:

- Red = Main Driving Light
- Black = Negative -VE
- Grey = White Position Light
- Yellow = Amber Position Light
- Green = Amber Warning Light



TECHNICAL SPECIFICATIONS

Type	Worklight Driving Lamp with Position / Amber Warning
Voltage	10-30VDC
LED's	Driving: 24 x 5W OSRAM LED, Pos 18LED's Amber 24LED's
Power	Driving: 120W, 18W Pos, 24W Amber
Current Draw	Driving 3.85A at 12V. Pos 0.043A at 12V, Amber 0.26A at 12V
Lumens / Lux	10,080 (3580 Effective). 2010 LUX at 10M
IP Rating	IP68 / IP69K
Material Construction	Aluminium with PC Lens. Bracket SS304
Weight	1.506Kg
Dimensions	Please see below
Operating Temperature	-30°C to +65°C
Storage Temperature	-40°C to +85°C
Certificate	CE, E Mark R10, R7, R65, R112

TECHNICAL DRAWING

